

## Technical Data Sheet

### 3mm Infrared LED SIR3065B



#### ■ Features

- High reliability
- High radiant intensity
- Peak wavelength  $\lambda_p=940\text{nm}$
- 2.54mm Lead spacing
- Low forward voltage
- Pb free
- The product itself will remain within RoHS compliant version.


#### ■ Descriptions

- SHUGUAN'S Infrared Emitting Diode(SIR3065B) is a high intensity diode , molded in a black plastic package.
- The device is spectrally matched with phototransistor , photodiode and infrared receiver module.

#### ■ Applications

- Free air transmission system
- Infrared remote control units with high power requirement
- Smoke detector
- Infrared applied system

## ■ Package Dimensions



Note: 1. All dimensions are in millimeters  
2. Tolerances unless dimensions  $\pm 0.25$ mm

## ■ Absolute Maximum Ratings (Ta=25°C)

| Parameter                                                   | Symbol           | Rating    | Units |
|-------------------------------------------------------------|------------------|-----------|-------|
| Continuous Forward Current                                  | I <sub>F</sub>   | 100       | mA    |
| Peak Forward Current                                        | I <sub>FP</sub>  | 1.0       | A     |
| Reverse Voltage                                             | V <sub>R</sub>   | 5         | V     |
| Lead Soldering Temperature                                  | T <sub>sol</sub> | 260       | °C    |
| Operating Temperature                                       | T <sub>opr</sub> | -40 ~ +85 | °C    |
| Storage Temperature                                         | T <sub>stg</sub> | -40 ~ +85 | °C    |
| Power Dissipation at(or below)<br>25°C Free Air Temperature | P <sub>d</sub>   | 150       | mW    |

Notes: \*1:I<sub>FP</sub> Conditions--Pulse Width  $\leq 100 \mu$ s and Duty  $\leq 1\%$ .

\*2:Soldering time  $\leq 5$  seconds.

### ■ Electro-Optical Characteristics (Ta=25°C)

| Parameter          | Symbol           | Condition                                   | Min. | Typ. | Max. | Units |
|--------------------|------------------|---------------------------------------------|------|------|------|-------|
| Radiant Intensity  | Ee               | IF=20mA                                     | 1.5  | 2.5  | ---  | mW/sr |
|                    |                  | IF=100mA Pulse Width<br>≤ 100 μs ,Duty ≤ 1% | ---  | 10   | ---  |       |
|                    |                  | IF=1A Pulse Width<br>≤ 100 μs ,Duty ≤ 1%.   | ---  | 68   | ---  |       |
| Peak Wavelength    | $\lambda_p$      | IF=20mA                                     | ---  | 940  | ---  | nm    |
| Spectral Bandwidth | $\Delta \lambda$ | IF=20mA                                     | ---  | 50   | ---  | nm    |
| Forward Voltage    | VF               | IF=20mA                                     | ---  | 1.2  | 1.5  | V     |
|                    |                  | IF=100mA Pulse Width<br>≤ 100 μs ,Duty ≤ 1% | ---  | 1.4  | 1.8  |       |
|                    |                  | IF=1A Pulse Width<br>≤ 100 μs ,Duty ≤ 1%.   | ---  | 2.6  | 4.0  |       |
| Reverse Current    | IR               | VR=5V                                       | ---  | ---  | 10   | μA    |
| View Angle         | 2θ 1/2           | IF=20mA                                     | ---  | 60   | ---  | deg   |

### ■ Typical Electro-Optical Characteristics Curves

Fig.1 Forward Current vs.  
Ambient Temperature




Fig.2 Spectral Distribution




Fig.3 Peak Emission Wavelength vs.  
Ambient Temperature




Fig.4 Forward Current vs.  
Forward Voltage




Fig.5 Radiant Intensity vs.  
Forward Current




Fig.6 Relative Radiant Intensity vs.  
Angular Displacement




Fig.7 Relative Intensity vs.  
Ambient Temperature (°C)





Fig.8 Forward Voltage vs.  
Ambient Temperature (°C)



Notes:

1. Above specification may be changed without notice. SHUGUAN will reserve authority on material change for above specification
2. When using this product , please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. SHUGUAN assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification